



### SANSWITCH-24POE

SANTEC Switch smart managed 24-Port  
PoE Fast Ethernet plus 2 Giga Combo Ports, 19"

#### PRODUCT DESCRIPTION

##### ► Application:

The SanSwitch-24POE offer 24-Ports 10/100Mbps + 2-Ports 10/100/1000Mbps (Gigabit) that lead you to a real gigabit connection. Users are now able to transfer high bandwidth-demanded files faster and get a real efficiency improvement with the user-friendly Web-based management interface. This product also equips 2 mini GBIC slots for your flexible fiber connection. Use of the mini-GBIC port disables the connection of its corresponding copper port automatically.

##### ► Technical specifications:

Type	PoE Switch
Number of Ethernet ports	24 + 2 SFP
Power over Ethernet (PoE)	Yes
Number of PoE ports	24
PoE standard	IEEE802.3at
Max. PoE Output Voltage (port)	PoE+ up to 30 watt per port
Max. PoE power consumption	500 W
Number of gigabit ports	2
Ethernet standards	10/100Base-T(PSE/PoE) 10/100/1000Base-T RJ-45/SFP
Ethernet connector	RJ-45
fibre optics	2x SFP Combo Port
Flow control	Yes IEEE 802.3x
Supported protocols	HTTP,HTTPS,FTP,SSH,SMTP,DNS,SNMP, IMAP,POP3 etc
VLAN	Yes, IEEE 802.1Q
QoS (quality of service)	Yes
LACP	IEEE 802.3ad

SANTEC BW AG  
An der Strusbek 31, 22926 Ahrensburg, Germany  
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10  
santec\_info@burg.biz, www.santec-video.com



### ► Technical specifications:

Buffer Memory	2,75 MB
Integrated web interface	Yes
Weight	4,7 kg
Voltage	100 - 240 V AC
Operating temperature (°C)	0 to +40
Rel. humidity (%)	10 - 90, non-condensing
Design	19" Rackmount
Rack mount (U)	1
Fan	Yes
Max. Power consumption (watt)	390
Dimensions WxHxD (mm)	440 x 220 x 44
Identifier	CE, FCC
Items included in delivery	Power cord, 19" bracket

### ► Weitere Bilder:

