



SANSWITCH-G8408

8-Port Gigabit Switch
managed, VLAN, QoS

PRODUCT DESCRIPTION

► Application:

The SanSwitch-G8408 is a powerful, high-performance Gigabit manageable Ethernet Switch, with all 8 ports capable of 10/100/1000Mbps auto-negotiation operation (NWay), which means the switch could automatically negotiate with the connected partners on the network speed and duplex mode. This switch supports PoE, which supplies power for connected devices via CAT 5 and above twisted cables. The PoE output can be managed individually on each port to provide best power to the PoE device.

► Technical specifications:

| | |
|----------------------------|---|
| Type | Gigabit Switch |
| Number of Ethernet ports | 8 |
| Ethernet standards | 10Base-T/100Base-TX/1000Base-TX |
| Ethernet connector | RJ-45 |
| Power over Ethernet (PoE) | No |
| PoE standard | - |
| Flow control | Yes |
| Supported protocols | QoS, VLAN, NWAY, SNMP |
| Switch capacity (Gbit/s) | 148810pps at 100Mbps, 1488095pps at 1Gbps |
| MAC address memory (KB) | 8192 |
| MAC address update | auto |
| RS-232 interface | Yes |
| Noise emission (dB) | 0 |
| Voltage | 100 - 240 V AC |
| Operating temperature (°C) | 0 to +40 |
| Rel. humidity (%) | 10 - 90, non-condensing |

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



► Technical specifications:

| | |
|-------------------------------|----------------|
| Design | Desktop |
| Rack mount (U) | 1 |
| Fan | No |
| Max. Power consumption (watt) | 12 |
| Dimensions WxHxD (mm) | 250 x 27 x 104 |
| Identifier | CE, FCC |
| Items included in delivery | Power cord, CD |