



## SCC-241KBIM

1080p HD-CVI IR-bullet camera  
2,7-12mm lens

### PRODUCT DESCRIPTION

#### ► Application:

SANTEC HD-CVI day/night dome camera for indoor and outdoor applications. Thanks to the integrated IR LEDs with up to 60m range and the manual zoom lens (2.7-12mm), this camera is equally suitable for day as well as for night applications. It has a resolution of 1080p.

#### ► Technical specifications:

Type	HD-CVI Day/Night IR bullet camera
Video signal	HD-CVI, CVBS (analogue)
Sensor	1/2.9" CMOS
Sensor type	1/2.9" CMOS
Effective pixel	1920x1080
Resolution	1080p
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	<65dB
Lens mount	Intern
Iris control	DC/manual
Lens type	Manual zoom lens
Focal length	2.7 - 12 mm
Angle of view (horizontal)	93° - 33°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.02 color / 0.0 Lux (IR-LED)
Aperture (max)	F1.4
Automatic gain control (AGC)	AGC

SANTEC BW AG  
An der Strusbek 31, 22926 Ahrensburg, Germany  
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10  
santec\_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Digital noise reduction (DNR)	2D
Shutter (sec.)	1/25 - 1/100.000
White balance	AWB / manual
Backlight compensation	BLC, HLC, DWDR
Wide dynamic range (WDR)	DWDR
Day/night mode adjustment	Auto / manual
Camera adjustments	OSD -> recorder menu
Auto focus	No
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Motion detection (zones)	Yes (via recorder)
Privacy zones	Yes, 4 zones
Camera title	Yes
Video output	BNC, 75 Ohm 1 Vpp
Switch input contacts	No
Switch output contacts	No
Control interface	HDCVI (coax)
Classification	IP-66
Vandal-proof	No
Installation	Wall mount, ceiling mount and pole mount
Camera mounting	Screw mounting
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR range (m)	up to 60
IR wave length	850
Voltage	12 V DC
Max. Power consumption (watt)	7,7
Operating temperature (°C)	-20 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxHxD (mm)	213 x 80 x 72
Weight	550 g
Identifier	CE, RoHS
Specials	Coaxtransmission up to 700m

► **Note:**

The range of the built-in IR-LEDs strongly depends on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► **Recommended Accessories**

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring
SNCA-MK-4532	Adapter / mounting kit for CVI cameras
SNCA-WM-4644	wall bracket for SNC-431FEIF, 211FDIA, SCC-241KDIA, SNC-231RZNA
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter
SNCA-MK-4537	Adapter/Junction box for SCC-241KBIM and SCC-251KBIA