



SCC-241KEIM

1080p HD-CVI IR-dome camera
2,7 - 12 mm manual zoom lens, IP-66

PRODUCT DESCRIPTION

► Application:

SANTEC HD-CVI day/night dome camera for indoor and outdoor applications. Thanks to the integrated IR LEDs with up to 30m range and the manual zoom lens (2.7-12mm), this camera is equally suitable for day as well as for night applications. It has a resolution of 1080p.

► Technical specifications:

Type	Day/night IR dome camera
Video signal	HD-CVI, CVBS (analogue)
Sensor	1/2,8"
Sensor type	1/2.8" Progressive scan CMOS
Effective pixel	1920x1080
Resolution	1080p
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	<65dB
Lens mount	Intern
Iris control	DC/manual
Lens type	Manual zoom lens
Focal length	2.7 - 12 mm
Angle of view (horizontal)	93° - 35°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.05 color / 0.0 Lux (IR-LED)
Aperture (max)	F1.4
Automatic gain control (AGC)	AGC

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/25 - 1/10000
White balance	AWB / manual
Backlight compensation	BLC, HLC, DWDR
Wide dynamic range (WDR)	DWDR
Day/night mode adjustment	Auto / manual
Camera adjustments	OSD -> recorder menu
Auto focus	No
Digital zoom	No
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Motion detection (zones)	Yes (via recorder)
Privacy zones	Yes, 4 zones
Camera title	Yes
Video output	BNC, 75 Ohm 1 Vpp
Switch input contacts	No
Switch output contacts	No
Control interface	HDCVI (coax)
Classification	IP-66
Vandal-proof	No
Installation	Ceiling mount
Camera mounting	Screw mounting
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR range (m)	up to 30
IR wave length	850
Voltage	12 V DC
Max. Power consumption (watt)	4,5
DORI max. (Detect-Observe-Recognize-Identify)	125m - 50m - 25m - 13m
DORI min. (Detect-Observe-Recognize-Identify)	49m - 20m - 10m - 5m
Operating temperature (°C)	-20 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxH (mm)	119 x 97
Weight	550 g
Identifier	CE, RoHS
Specials	Coaxtransmission up to 700m



SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Note:

The range of the built-in IR-LEDs strongly depends on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring
SNCA-WM-204W	Wall bracket for SNC-431FEIF, SNC-431FDIF
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter