



SNC-211RLNA

SANTEC 2 MP IP-Box camera
4,3-129mm 30x zoom-lens, PoE

PRODUCT DESCRIPTION

► Application:

SANTEC SNC-211RLNA is an IP camera in box design which produces excellent images at 2 megapixel resolution. Features like multi-streaming, region of interest (ROI), PoE and micro-SD card slot are of course included. SNC-211RLNA is a camera which can be universally used, i.e. indoors as well as outdoors using a matching weather-proof housing.

► Technical specifications:

Type	IP Day/Night box camera
Sensor type	1/2.8" Progressive Scan Exmor CMOS
Picture resolution (pixel)	2 MP (1920x1080)
Video codec	H.264, H.265, MJPEG
Max. frame rate (fps)	50/60 at 1080P
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Iris control	Auto/manual
Lens type	Int. 30x motorzoom
Focal length	4,5 - 135 mm, F1.6-F4,4
Angle of view (horizontal)	67.8° - 2.4°
Sensitivity (Lux)	0,005/F1.6 (color) / 0,0005/F1.6 (b/w)
IR cut filter	IR-Cut filter (mechanical)
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/1 - 1/30,000

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

White balance	Auto / ATW / indoor / outdoor / manual
Backlight compensation	BLC, HLC, WDR
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Digital zoom	Yes
Mirroring (vertical)	Yes
Privacy zones	24
Motion detection	Yes
Region of Interest (ROI)	Yes
Camera title	Yes
Intelligent Video Analysis (IVA)	IVA+
Audio support	Yes
Audio in-/outputs	1 / 1
Audio codec	G.711a / G.711Mu / PCM
Alarm contacts I/O	2 / 1
RS-485 interface	Yes, 1x
Alarm management	HTTP, FTP, SMTP
Schedule	Yes
Management software support	Many VMS
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP, UDP, UPNP, BONJOUR, DHCP, FTP, SMTP, RTSP
Supported software standards	ONVIF, PSIA, CGI
Internal memory	SD Karte (internal / optional)
Ethernet connector	RJ-45
Ethernet standards	10/100 Base-T
Classification	-
Housing colour	White
Housing material	Aluminium
IR distance (m. ca.)	No IR-LED
Voltage	12 V DC, PoE
PoE standard	IEEE 802.3af
Max. Power consumption (watt)	10
DORI max. (Detect-Observe-Recognize-Identify)	1862m - 744m - 372m - 185m
Operating temperature (°C)	-20 to +60
Storage temperature (°C)	0 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxHxD (mm)	70 x 70x 160
Weight	1000 g
Identifier	CE, RoHS
Items included in delivery	CD, software, user manual
Specials	30x optical zoom, EIS, SVC, LowLight, H.265

► SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



Note:

The SD card is not included in the delivery.

► **Recommended Accessories**

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
HEL-62D	SANTEC weather-proof housing, aluminium sunshield, IP-66
HPV42K2A700	Videotec Housing with IPM Module Camera Housing for IP-cameras
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter
SANPOWER-MS01BL	1-channel 30 W PoE power injector 56V, 30 W