



SNC-441RBIAE

4MP IR-bullet,H.265(+),TrueWDR,video analysis,PoE
2,7-13,5 mm lens, IP66

PRODUCT DESCRIPTION

► Application:

Die SANTEC BW Kameras der SNC-441-E Serie, verfügen über ein ePoE Modul, mit dem eine Netzwerkübertragung von bis zu 400m erreicht wird. Zudem kann mittels H.265 (+) Codec, die benötigte Bandbreite, bei gleicher Bildqualität, nahezu halbiert werden. Dank der erweiterten Video Analyse Funktionen kann die Kamera universell für Überwachungsaufgaben, in Bereichen wie Retail, Objektüberwachung, Produktionsüberwachung, etc. eingesetzt werden. Die leistungsstarke Hardware wurde mit einem neuen Bildsensor für brillante Farben, einem mehr als viermal so schnellen DSP und doppelt soviel Arbeitsspeicher wie das Vorgängermodell ausgestattet.

► Technical specifications:

Type	IP day/night dome camera
Sensor type	1/3" Progressive Scan CMOS
Picture resolution (pixel)	4 MP (2688x1520)
Video codec	H.264, H.265, MJPEG, H.264+, H.265+
Max. frame rate (fps)	25 fps@4MP
Number of video streams	3 (1x Main, 2x Sub)
Lens mount	Intern
Iris control	DC
S/N ratio (dB)	< 50dB
Lens type	5x autofocus lens
Focal length	2,7 - 13,5 mm / F1.4
Angle of view (horizontal)	100° - 35°
Angle of view (vertical)	54° - 20°
Sensitivity (Lux)	0,05lx (color)

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Sensitivity (Lux)	0Lux (IR on)
IR cut filter	IR-Cut filter (mechanical)
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/3 - 1/100,000
White balance	Auto / sunny / night / outdoor / manual
Backlight compensation	BLC, HLC, WDR(120dB)
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Digital zoom	16x, adjustable
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Privacy zones	Yes, 4 zones
Region of Interest (ROI)	Yes, 4 zones
IVA via ONVIF Motion	Yes
People counting (IVA+)	Yes
Heatmap (IVA+)	Yes
Tripwire (IVA)	Yes
Intrusion (IVA)	Yes
Tampering Alarm	Yes
Scene change (tampering)	Yes
IVS Missing / Added	Yes
Audio detect (IVA)	Yes
Face detect (IVA)	Yes
Motion detection	Yes, 4 zones
Camera title	Yes
Video output	Yes
Audio support	Yes
Audio in-/outputs	1 / 1
Audio codec	G.711a / G.711Mu / AAC / G.726
Alarm contacts I/O	2 / 1
Alarm management	HTTP, FTP, SMTP, ONVIF
Schedule	Yes
Management software support	Many VMS
Supported browser	Internet Explorer 11
BURG-WÄCHTER cloud	Yes
Smartphone App	BurgCam App
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP, TCP, NTP, IPv4, IPv6, DHCP, TELNET, ONVIF, FTP
Supported software standards	ONVIF, PSIA, CGI
Internal memory	Micro SD (optional), max. 128 GB
Video Content Analytics (VCA)	Tripwire, Intrusion, Face detect, etc.
Ethernet connector	RJ-45
Ethernet standards	10/100Base-T

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Classification	IP-66
Vandal-proof	No
Heater	No
Installation	Wall and ceiling mount
3 axis	yes
Camera mounting	Screw mounting
Housing colour	White
Housing material	Metal / Plastic
Integrated IR-LEDs	Yes, Smart IR, off, manual
Wavelength IR-LED	850 nm
IR-LED illuminant	4
IR distance (m. ca.)	50
DORI max. (Detect-Observe-Recognize-Identify)	208m - 83m - 41m - 20m
DORI min. (Detect-Observe-Recognize-Identify)	64m - 26m - 13m - 6.5m
Voltage	12 V DC, PoE
PoE standard	IEEE802.3at
ePoE	Yes, up to 400m (with ePoE switch)
Max. Power consumption (watt)	<11,5
Operating temperature (°C)	-30 to +60
Storage temperature (°C)	0 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxHxD (mm)	95 x 95 x 280
Weight	1070 g
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide
Specials	Cable distance up to 400m (with ePoE switch)

► **Note:**

Eine SD-Karte ist nicht im Lieferumfang enthalten. Die Reichweite der IR- Strahler ist stark abhängig vom Einsatzort und von der Umgebung. Stark absorbierende Flächen, wie z.B. dunkle raue Strukturen (Boden, Rasen, Asphalt) können zu einer deutlichen Verringerung der maximalen Reichweite führen.

► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
SANPOWER-MS01L	1-channel PoE power supply 48V DC
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter
SNCA-MK-4530	Adapter / Junction box for suitable for SANTEC cameras
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
SNCA-CM-4670	Corner Mount Adapter for see recommended accessories
SANSWITCH-10430	4-Port ePoE Switch For transmission over 800m