

SML-2212H

SANTEC 22" CCTV 6 in 1 plastic-monitor, 1920x1080, 60Hz, CVBS,CVI,TVI,AHD,VGA,HDMI

PRODUCT DESCRIPTION

Application:

The new monitors of the SML series have a timeless design and are equipped with professional technology

► Technical specifications:

Type	Lcd monitor
Screen diagonal	21.5" (54.6 cm)
Video signal	PAL, NTSC
Resolution pixel	1920x1080
Pixel dot pitch (mm)	0.2482(H) x 0.2482(V)
Picture format	16:9
Colours	16.7M
Brightness (cd/m2)	250
Contrast ratio	1000:1
Refresh rate (ms)	5
Visible area (H/V) mm	476.64(H) x 268.11(V)
View angle R/L and U/D in °	88/88 - 75/75
Operating Frequency	30-85 KHz(H) / 50-75Hz(V)
Background lighting	LED
Video inputs	1x BNC (CVI/TVI/AHD), 1x BNC-CVBS (analogue)
Video outputs (BNC)	1x BNC (CVI/TVI/AHD), 1x BNC-CVBS (analogue)
PC video input	VGA, HDMI
POP (picture-on-picture) function	No
PIP (picture-in-picture) function	No
Audio inputs	2x 3.5 mm (phone jack) (BNC-IN/PC-IN)

SANTEC BW AG

An der Strusbek 31, 22926 Ahrensburg, Germany Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10 santec_info@burg.biz, www.santec-video.com



MONITORS SML SERIES

SML-2212H

► Technical specifications:

Speakers	2x 3W
OSD menu languages	Multi language
Control OSD	Buttons on front
Installation option	VESA / MIS-D 100x100
Housing colour	Black
Housing material	Plastic
Voltage	12 V DC using external power supply 230VAC/2A
Max. Power consumption (watt)	20
Operating temperature (°C)	-10 to +50
Rel. humidity (%)	20 - 70, non-condensing
24/7 operation	Yes
Dimensions WxHxD (mm)	507 x 309,1 x 22 (without mounting)
Dimensions mounting stand	250,1 x 61,1 x 149,1
WxHxD (mm)	
Weight	4,2 Kg
Identifier	CE
Items included in delivery	Power supply 12VDC, remote control

Note:

Available at the end of May

Recommended Accessories

VA-3240	LCD-Monitor wall mount black/silver up to 24", max. wall dist. 537mm, max.
	load 32 kg
VA-VESA-171	VESA wall bracket for monitor 7.5x7.5/10x10cm, wall distance 7.4 cm

