



SFC-241KBIAS

SANTEC Stainless Steel 4in1 IR bullet camera
2,8-12 mm mot.zoom-lens,CVI,TVI,AHD,CVBS,12vdc

PRODUCT DESCRIPTION

► Application:

SANTEC HD-CVI day/night dome camera for indoor and outdoor applications. Thanks to the integrated IR LEDs with up to 30m range and the motorized vario lens (2.8-12mm), this camera is equally suitable for day as well as for night applications. It has a resolution of 1080p.

► Technical specifications:

Type	Day/night IR bullet camera
Video signal	HD-CVI, TVI, AHD, CVBS (analogue)
Sensor	1/2,8"
Sensor type	1/2.8" Progressive Scan Exmor CMOS
Horizontal resolution (TVL)	1080p / 960H
Effective pixel	1920x1080
Max. frame rate (fps)	25
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	< 65 dB
Lens mount	Intern
Iris control	Auto/manual
Lens type	4x autofocus lens
Focal length	2,8 - 12 mm
Angle of view (horizontal)	87° - 31° (HD-Mode)
IR cut filter	ICR-IR-Cut filter
Sensitivity (Lux)	0,5 (color), 0,0 Lux (IR-LED)
Aperture (max)	F1.4

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	3D DNR
White balance	AWB / manual
Backlight compensation	BLC, HLC, DWDR
Day/night mode adjustment	Auto / color / B/W
Camera adjustments	OSD -> recorder menu
Auto focus	Automatic / manual
Optical zoom	4x, adjustable
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Motion detection (zones)	Yes (via recorder)
Privacy zones	Yes, 4 zones
Camera title	Yes
Video output	BNC, 75 Ohm 1 Vpp
UTP (twisted pair)	No
Switch input contacts	No
Switch output contacts	No
Control interface	No
Control protocols	HDCVI
Classification	IP-68
Vandal-proof	Yes, acc. to IK10
Installation	Wall mount, ceiling mount and pole mount
Camera mounting	Screw mounting
Housing colour	Silver
Housing material	Stainless steel
Integrated IR-LEDs	Yes
IR range (m)	up to 30
IR wave length	850
IR-LED illuminant	2
Voltage	12 VDC (+/-10%)
Max. Power consumption (watt)	5
DORI max. (Detect-Observe-Recognize-Identify)	133m - 53m - 27m - 13m
DORI min. (Detect-Observe-Recognize-Identify)	48m - 19m - 10m - 5m
Operating temperature (°C)	-20 to +50
Rel. humidity (%)	Max. 85, non-condensing
Dimensions WxHxD (mm)	104,0 x 120,0 x 126,0
Weight	1,52 kg
Identifier	CE, RoHS

► **SANTEC BW AG**

An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Note:

The range of the built-in IR-LEDs strongly depends on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring